# Progress Toward an NCI<sub>3</sub>-Fueled lodine Laser

# William McDermott,\* Robert Coombe, Julanna Gilbert, Zane Lambert, and Mikaila Heldt

University of Denver Research Institute, 2050 East Iliff Avenue, Denver, Colorado 80208

The NCl-I laser has been demonstrated by using  $HN_3$  as a fuel. We discuss the possibility of constructing a  $NCl(a^t\Delta)$ -I transfer laser by using  $NCl_3$  as a fuel. Not only is  $NCl_3$  more stable but it also may eliminate the requirement for a combustor. We present kinetic modeling and the results of experiments designed to understand the basic physical processes in this system. Experiments have included determination of the time profile history of NCl(a), NCl(b),  $I^*$ , and chlorine recombination. The efficiency of production of chlorine atoms in a microwave discharge has been measured. We have also shown that the autodecomposition of  $NCl_3$  can be initiated by modest heating of the  $NCl_3$  flow, which supports our belief that a combustor will not be required. The NCl-I laser operates on gas species, eliminating the need for heterogeneous gas-liquid reactions such as used for the production of COlL chemical lasers. The lasing species is the same as in COlL, simplifying the scaling process since many optical, tracking, and propagation problems have been demonstrated in the ABL program. This work is supported by the JTO through the AFOSR-administered MRI program.

KEYWORDS: Chemical laser, NCl-I transfer laser, NCl3 reactions

#### 1. Introduction

The level structure of the  $NCl(a^1\Delta)$  molecule is identical to the structure of  $O_2(^1\Delta)$  since the two molecules are isoelectronic. As such, the molecule would be expected to be metastable and capable of transferring it's energy to the iodine atom as does  $O_2(^1\Delta)$  in the chemical oxygen iodine laser. In fact, lasers have been demonstrated by using the energy transfer from  $NCl(a^1\Delta)$  to iodine atoms.<sup>2,3</sup> These lasers produce  $NCl(a^1\Delta)$  from the reaction of chlorine atoms and hydrogen azide. Not only are chlorine atoms difficult to produce (requiring a combustor), but hydrogen azide is in itself extremely unstable. We reviewed the development of this laser in previous papers.<sup>6</sup> Our approach is to look at the possibility of using  $NCl_3$  as a fuel replacing  $HN_3$  and perhaps eliminating the need for a chlorine atom source. At Denver University, we have shown that the combustion of  $NCl_3$  by hydrogen atoms produces  $NCl(a^1\Delta)$  in high yield.<sup>1</sup> We used a microwave discharge to produce hydrogen atoms in those studies. A more recent study at Physical Sciences, Inc., has observed the pumping of iodine atoms by  $NCl(a^1\Delta)$  and a resulting decrease in the optical absorption in the H-atom-initiated system.<sup>4</sup> In this study, we are looking at the

Received December 5, 2004; revision received March 5, 2005.

<sup>\*</sup>Corresponding author; e-mail: wmcdermo@du.edu.

Species	Concentration (1/cm <sup>3</sup> )	Pressure (torr)	Mole fraction
Ar	5.62E+16	1.73	73.20%
$Cl_2$	1.18E + 14	0.00	0.15%
C1	7.86E + 13	0.00	0.10%
$NCl_3$	4.09E + 13	0.00	0.05%
HI	$0.00E\!+\!00$	0.00	0.00%
$H_2$	2.03E + 16	0.63	26.49%
Total	7.67E + 16	2.37	

**Table 1.** Typical operating conditions

chlorine-atom-initiated decomposition of NCl<sub>3</sub> as a source of NCl( $a^1\Delta$ ). We are comparing the time profiles of various species to model predictions to evaluate the kinetic model.

## 2. Experimental Setup

The experimental apparatus has been described in previous papers.<sup>6</sup> Briefly, we have a flexible flow system that allows us to inject reactants in several places and measure the emissions from various species as a function of time from the injection points. Typical operating conditions without the addition of HI are given in Table 1.

The flow velocity is about 900 m/s. The NCl<sub>3</sub> is produced in a hood under several layers of protection and carried with argon to the experimental apparatus. The concentration of NCl<sub>3</sub> is measured by absorption at 254 nm (Hg pen lamp) and recorded by using LabView. The amount of argon and NCl<sub>3</sub> admitted to the flow system is usually measured by replacement of a small auxiliary flow of argon. That is, the argon makeup flow is decreased by the desired flow rate, and then argon and NCl<sub>3</sub> are introduced to return to the original pressure. This procedure allows flow measurement without risking the decomposition of the NCl<sub>3</sub> in the flow meter. When HI is flowed to produce I atoms, the HI is added from a bulb diluted to about 5% in argon. The total flow is measured with a flow meter and typically results in an HI concentration of about  $8 \times 10^{13}$  cm<sup>-3</sup>.

#### 3. Results

Our typical experimental setup mixes chlorine atoms (and undissociated chlorine molecules) into a flow of argon and NCl<sub>3</sub>. After 5  $\mu$ s, H<sub>2</sub> or a mixture of H<sub>2</sub> and HI is added to the flow. The initial reaction between Cl atoms and NCl<sub>3</sub> should dissociate the NCl<sub>3</sub> into NCl<sub>2</sub>. Reaction of H<sub>2</sub> with excess Cl atoms produces H atoms (and HCl). The H atoms then react with the NCl<sub>2</sub> to produce NCl(a<sup>1</sup> $\Delta$ ). To quantify the chlorine atom concentration, we measured the dissociation of chlorine by titrating the flow from the microwave discharge with HI and observing the excited HCl produced on an IbSb detector fitted with a filter that passes the HCl fundamental emission. The HI and Cl atom reaction is fast, and so monitoring the HCl emission at a point a few microseconds downstream of the mixing point is adequate. A typical titration experiment is shown in Fig. 1.

The average dissociation fraction was about 25%, in good agreement with the work of Manke and Setser.<sup>5</sup> The discharge was coupled to the chlorine flow (5% chlorine in




Fig. 1. HCl fundamental emission as a function of added HI.




Fig. 2. Fraction of chlorine dissociated versus absorbed power.

argon) with a McCarron cavity and a ceramic discharge tube. Titrations were done at high microwave power ( $\sim 100$  W, < 5 W reflected). There appeared to be a suggestion of microwave power dependence (Fig. 2). The microwave absorbed power is the difference between forward and reflected power.

In our previous paper, we noted that the rise time of the  $NCl(a^1\Delta)$  emission seemed slower than predicted. We measure the  $NCl(a^1\Delta)$  by using an intrinsic Ge detector with a 1.08- $\mu$ m

narrow-band-pass filter. At early times, we noted the appearance of  $Cl_2(B-X)$  radiation in the visible, which might contribute to the signal at 1.08  $\mu m$  since the recombination radiation extends well into the near IR. To evaluate this contribution, we measured the  $Cl_2(B-X)$  in the visible by using an 0.85- $\mu m$  long pass filter and a visible (GaAs) photomultiplier




Fig. 3. Comparison of model and uncorrected 1.08- $\mu$ m emission.




Fig. 4.  $NCl(a^1\Delta)$  and  $Cl_2$  (B-X) normalized emissions.




Fig. 5.  $NCl(a^1\Delta)$  with  $Cl_2$  (B-X) emission subtracted.




Fig. 6. Variation of I\* signal with NCl<sub>3</sub> flow rate.

tube (PMT). This combination acted as a broadband (0.85–0.90  $\mu m$ ) filter because the PMT sensitivity drops off sharply at around 0.90  $\mu m$ . Figure 4 compares these two emissions. The appearance of recombination radiation at an early time makes the NCl(a<sup>1</sup> $\Delta$ ) rise time look much slower than it is. Figure 5 compares the kinetic model with the corrected NCl(a<sup>1</sup> $\Delta$ ) emission. Although the production rate of NCl(a<sup>1</sup> $\Delta$ ) is slower than predicted, the fall time agrees well with model predictions.




Fig. 7. Variation of I\* signal with H<sub>2</sub> flow rate.




Fig. 8. Variation of I\* signal with Cl<sub>2</sub> flow rate.

Recently, we have conducted experiments adding HI to the reaction mixture. The HI is added (carried in argon) into the  $H_2$  flow. Figure 6 shows that the  $I^*$  signal is linear in the NCl<sub>3</sub> flow rate. Variation of the hydrogen (Fig. 7) and chlorine (Fig. 8) are linear at lower concentrations and reach a peak at higher additions. This indicates that NCl<sub>3</sub> is probably the limiting reactant in these experiments.

The time profile of the I\* signal was unusual. It appears to reach a peak value about 20 ms after HI injection, which agrees with the location of the maximum  $NCl(a^1\Delta)$  concentration (see Fig. 5). The time profile includes a substantial contribution from  $Cl_2(B-X)$  at an early time (Fig. 9).




Fig. 9. Time profile of I\*. Data are indicated by the points. The Cl<sub>2</sub> emission is scaled.

We see a similar trend in the emission at 1.315- $\mu$ m when HI is absent. This emission is much smaller than the I\* emission and is also likely due to chlorine recombination.

### 4. Model Calculations

Our kinetic model currently includes 29 rate constants. They are detailed in Ref. 7. We have updated our model to include the recent work at Emory University,<sup>8</sup> which gives new quenching rate constants for  $H_2$ , HCl,  $Cl_2$ , and  $O_2$ . A reinvestigation of these rates was necessary since earlier studies using  $ClN_3$  as a source assumed that  $NCl(a^1\Delta)$  was a primary product of the photodissociation of  $ClN_3$ . It was recently shown that the primary product channel is fragmentation to  $Cl + N_3$  and production of  $NCl(a^1\Delta)$  occurs as a subsequent reaction.<sup>9</sup> In all cases, the new quenching rate is significantly slower than the old rate. The rise time of the NCl(a) emission is determined by the rate of the two production reactions:

$$H + NCl_3 \rightarrow NCl_2 + HCl$$
  
 $H + NCl_2 \rightarrow NCl(a) + HCl$ 

The fall time is governed by the quenching of NCl(a). The assumed rates for each of these processes are given in the reference cited above. Absolute densities are not available in the flow system due to the difficulties in absolute intensity measurements. We plan to use an infrared optical multichannel analyzer in future experiments to measure the relative yield of  $I^*(^2P_{1/2})$  from NCl(a).

# 5. Acknowledgments

This program is supported by the Air Force Office of Scientific Research through the Multidisciplinary Research Initiative (MRI) program. The Air Force Program Manager is Dr. Mike Berman. The author credits many useful discussions with other members of the MRI team. They include Dr. Tom Henshaw and Dr. Dave Neumann of Directed Energy Solutions; Dr. Steve Davis of Physical Sciences, Inc., and Dr. Mike Heaven and Dr. Keiji Morokuma of Emory University.

## References

- <sup>1</sup>Exton, D.B., J.V. Gilbert, and R.D. Coombe, J. Phys. Chem. 95, 2692 (1991).
- <sup>2</sup>Henshaw, T.L., G.C. Manke, H. T.J. Madden, G.D. Hager, and M.R. Berman, "A New Chemically Pumped I ( $^2P_{1/2}$ - $^2P_{3/2}$ ) Laser at 1.315  $\mu$ m," *Proceedings of the 23rd International Conference on Lasers*, Vol. 23, p. 127 (2000).
- <sup>3</sup>Henshaw, T.L., G.C. Manke, II, T.J. Madden, M.R. Berman, and G.D. Hager, Chem. Phys. Lett. **325**(5,6), 537 (2000).
  - <sup>4</sup>Hunter, A.J.R., W.J. Kessler, S. Lec, and S.J. Davis, Proc. SPIE **5334** (2004).
  - <sup>5</sup>Manke, G.C., II, and D.W. Setser, J. Phys. Chem. **102**, 153 (1998).
  - <sup>6</sup>McDermott, W.E., R.D. Coombe, J.V. Gilbert, R. Van Allen, and M. Heldt, Proc. SPIE **4971** (2003).
  - <sup>7</sup>McDermott, W.E., R.D. Coombe, J.V. Gilbert, Z. Lambert, and M. Heldt, Proc. SPIE 5334 (2004).
  - <sup>8</sup>Tinney, S.P., J. Han, and M.C. Heaven, Proc. SPIE **5334** (2004).
- <sup>9</sup>Wodtke, A.M., N. Hansen, J.C. Robinson, N.E. Sveum, S.J. Goncher, and D.M. Neumark, Chem. Phys. Lett. **391**, 334 (2004).

#### The Authors

**Dr. Robert Coombe** is the Chancellor of the University of Denver and a Professor in the department of Chemistry and Biochemistry at DU. Dr. Coombe was raised in Denver and educated in the Denver Public Schools. He holds a B.A. degree from Williams College and a Ph.D. (in Chemistry) from the University of California at Berkeley. After a postdoctoral research appointment at the University of Toronto, he worked for several years as a research scientist at the Rockwell International Science Center in Thousand Oaks, California, before joining the University of Denver as a faculty member in 1981. Apart from teaching and research in the Chemistry and Biochemistry department, Dr. Coombe has served the University as Chair of that department and as Dean of the division of Natural Sciences, Mathematics, and Engineering. He has been Provost of the University since 2001.

**Dr. Julanna Gilbert** is the Director of the Center for Teaching and Learning and a faculty member in the Department of Chemistry and Biochemistry at the University of Denver. Her research interests have involved kinetic and spectroscopic studies of energetic inorganic compounds using low-temperature matrix isolation and gas phase methods. Molecules of interest include the halogen amines, halogen azides, and boron–nitrogen systems.

Ms. Mikalia Heldt was a graduate student in the Department of Chemistry and Biochemistry at Denver University.

**Mr. Zane Lambert** was a graduate student in the Department of Chemistry and Biochemistry at Denver University.

**Dr. William McDermott** is a Senior Research Scientist at the Denver Research Institute. He received his Ph.D. in Applied Science at the University of California at Davis in 1968. He has worked in various research and development positions for the U.S. Air Force including radiochemistry, teaching chemistry, chemical laser research, and space system engineering and management. Upon retirement from the Air Force, he has worked as Chief Operating Officer for a small business and as a Senior Scientist for Boeing. He is the inventor of the chemical oxygen iodine laser. He also has an M.B.A. degree from Auburn University.